

DS-K1F600-D6E-x Enrollment Station



DS-K1F600-D6E

DS-K1F600-D6E-F

The DS-K1F600-D6E-x Enrollment Station registers the information of multiple users on a single device. It can enroll information such as face pictures, fingerprints (DS-K1F600-D6E-F model), 13.56 MHz IC cards, and 125 KHz ID cards.

Available Models:

DS-K1F600-D6E

DS-K1F600-D6E-F

- 3.97-inch LCD Touch Screen
- 2 MP Dual Wide-Angle Lens
- Face Recognition Distance: 0.3 to 3 m
- Deep Learning Algorithm
- Face Recognition <0.2 s/User; Accuracy Rate ≥99%
- 2,000 User Capacity, 2,000 Face Capacity, 20,000 Card Capacity and 20,000 Fingerprint Capacity
- Enrolls Data via the Device and Transmits the Data from the Device to the Platform via the TCP/IP Protocol
- Enrolls Data Remotely via Client Software
- Stand-Alone Operation
- Manage/Search/Set Device Data Locally After Device Login

Specifications

	DS-K1F600-D6E	DS-K1F600-D6E-F
System		
Operating System	Linux	
Screen		
Dimensions	3.97"	
Resolution	800 x 480	
Type	Capacitive	
Operation Method	Touch	
Video		
Pixels	2 MP	
Lens	2	
WDR	Supported	
Video Standard	NTSC	
Audio		
Audio Output	Supported	
Volume Adjustment	Supported	
Network		
Wired Network	TCP/IP	
Wi-Fi	Supported	
Interface		
Power Interface	Round	
USB	1	
PSAM Card	Reserved	
Capacity		
User Capacity	2,000	
Card Capacity	20,000 (the display capacity on the device screen varies according to the configured enrollment rules)	
Face Capacity	2,000	
Fingerprint Capacity	--	20,000 (10 fingerprints per person)
Event Capacity	2,000 offline enrollment records	
Authentication		
Card Type	EM card and Mifare 1 card	
Card Reading Frequency	13.56 MHz, 125 KHz	
Card Reading Distance	0 to 5 cm	
Face Recognition Distance	0.3 m to 1.5 m	
Function		
Face Anti-Spoofing	Supported	
Audio Prompt	Supported	
M1 Card Encryption	Supported	
Time Synchronization	Supported	
Other		
Supplement Light	Supported	
Indicator	Not supported	
Power Supply	12 VDC, 15 W	
Working Temperature	14° F to 122° F (-10° C to 50° C)	
Working Humidity	10 to 90%	
Dimensions	4.8" x 5.4" x 4.9" (121.6 mm x 137.9 mm x 125 mm)	
Application Environment	Indoor	
Weight	1.1 lbs (0.5 kg)	
Installation	Base mount	

Dimensions

