

DS-K5032-3XFD

Temperature Screening Visitor Terminal

Hikvision's DS-K5032-3XFD Visitor Terminal features the Android operating system with dual screens. Temperature measurement range is 30° to 45° C (86° to 113° F) with 0.1° C accuracy and deviation of ±0.5° C. Other features include paperless enrollment and real-time counting for the current day.

The DS-K5032-3XFD can be used standalone or in a network.

- **Android™ Operating System with Dual-Screen Design**
- **Measurement Range: 30° to 45° C (86° to 113° F), 0.1° C Accuracy, Deviation: ±0.5° C**
- **Recognition Distance: 1 ft to 6 ft 7 in (0.3 m to 2 m)**
- **Fast Temperature Measurement**
- **Paperless Enrollment**
- **Real-Time Counting for Current Day**
- **Standalone and Networking Application, TCP/IP and Wi-Fi for Networking Application**
- **Standalone Management and Central Management(HikCentral V1.7)**
- **Up to 130,000 Visitor Records Can Be Stored on Device**

Available Model
DS-K5032-3XFD



Specifications

DS-K5032-3XFD	
System	
Operating System	Android 7.1.2
Temperature Measurement	
Temperature Range	30° to 45° C (86° to 113° F)
Sensor	Vanadium oxide uncooled sensor
Resolution	120 × 160
Frame Rate	25 fps
Measurement Accuracy	0.1° C
Measurement Deviation	±0.5° C, without black body calibration
Measuring Distance	0.3 m to 2 m
Screen	
Size	For administrator: 10.1-inch LCD touch screen; For visitor: 10.1-inch display screen
Resolution	1280 × 800
Camera	
Pixel	2 MP
Lens	2
WDR	Supported
Audio	
Audio Output	Built-in loudspeaker
Network	
Wired Network	10/100/1000 M self-adaptive
Wi-Fi	Supported
Interface	
Network Interface	1
Power Interface	Round
USB	2
Capacity	
Visitor Record	130,000
Authentication	
Card Type	Mifare 1 card
Card Reading Frequency	13.56 MHz
Card Reading Distance	0 cm to 4 cm
Card Reading Duration	<1 s
Others	
Indicator	Supported
Power Supply	12 VDC/3 A (included)
Working Temperature	-10° to 50° C (14° to 122° F)
Working Humidity	10% to 90% (non-condensing)

Dimensions

