

ECT-B12x

2 MP Outdoor EXIR Bullet Camera

TurboHD™



- 2 MP High Performance CMOS
- Up to 1920 x 1080 Resolution
- Ultra-Low Light
- 2.8 mm, 3.6 mm, and 6 mm Fixed Lens Options
- EXIR 2.0 up to 65 ft (20 m) IR Range
- IP66 Protection

The Hikvision ECT-B12x Outdoor EXIR Bullet Camera provides high definition analog output. TurboHD means that the analog signal can be sent over existing coaxial cable, eliminating the need to run new cables for high definition video.

EXIR 2.0 is Hikvision's proprietary IR extended range technology, which has a range of 65 feet (20 meters).

The 2.8 mm, 3.6 mm, and 6 mm fixed lens options are optimized for viewing angles that fit any situation.

Available models:

ECT-B122: 2.8 mm lens
ECT-B123: 3.6 mm lens
ECT-B126: 6 mm lens



Specifications

ECT-B12x	
Camera	
Image Sensor	2 MP CMOS image sensor
Signal System	NTSC
Effective Pixels	1920 (H) x 1080 (V)
Minimum Illumination	0.01 Lux @ (f1.2, AGC on), 0 Lux with IR
Shutter Speed	1/25 (1/30) s to 1/50,000 s
Lens	2.8 mm, 3.6 mm, and 6 mm fixed lens options
Horizontal Field of View	92° (2.8 mm), 70.9° (3.6 mm), 56.7° (6 mm)
Lens Mount	M12
Day / Night	IR cut filter
Angle Adjustment	Pan: 0° to 360°, Tilt: 0° to 180°, Rotation: 0° to 360°
Synchronization	Internal synchronization
Video Frame Rate	1080p @ 25 fps / 1080p @ 30 fps
HD Video Output	1 analog HD output
S/N Ratio	> 62dB
Interface	
Video Output	1 HD analog output
Switch Button	TVI/AHD/CVI/CVBS
General	
Operating Conditions	-40° F to 140° F (-40° C to 60° C), humidity: 90% or less (non-condensation)
Power Supply	12 VDC ± 25%
Power Consumption	Maximum 4 W
Protection Level	IP66
Material	Metal
IR Range	Up to 65 ft (20 m)
Dimensions	6.50" x 2.44" x 2.28" (165 mm x 62 mm x 58 mm)
Weight	Approximately 0.88 lbs (400 g)

Accessories



Dimensions

