

ELEVATED SKIN-SURFACE TEMPERATURE SCREENING SOLUTIONS



GOOD			
KEY FEATURES 0.9° F Accuracy Excellent Portability Affordable		Mid-range Handheld Camera DS-2TP21B-6AVF/W Effective Range: 3.3 to 6.6 ft.	The handheld thermographic camera is a good mobile screening solution with temperature measurement accuracy of $\pm 0.9^\circ$ F. The effective measurement distance range is 3.3 to 6.6 ft., which can satisfy social distancing requirements when held in hand. Built-in audible and visual highlight alarms notify the operator when an elevated temperature is detected. The camera can also be readily mounted on a tripod and remotely monitored over Wi-Fi using Hikvision's free desktop app or free mobile app.
		Free Desktop App iVMS-4200	iVMS-4200, a free, feature-rich video management software, provides a remote visual interface for monitoring thermographic and other surveillance cameras on computers with Windows operating systems.
		Free Mobile App Hik-Thermal	Hik-Thermal mobile client for Android, iPad and iPhone provides live remote monitoring and control of Hikvision thermographic temperature measurement devices. Take live measurements and record snapshots and video from a mobile device.

BETTER			
KEY FEATURES 0.9° F Accuracy Smart Measurement Mask Enforcement Automated Voice Alarms Rapid Screening		Short-range Turret Camera DS-2TD1217B-3/PA Effective Range: 2.6 to 4.9 ft.	The short-range turret and mid-range bullet cameras can be mounted on a tripod for a portable solution or affixed to a wall or ceiling for a long-term solution. The cameras can measure skin-surface temperature of up to 30 faces at one time, providing faster, more accurate screening. Additional features include face mask detection and automated voice alarms. Limiting temperature measurements solely to detected faces reduces false alarms from other heat sources such as a cup of coffee.
		Mid-range Bullet Camera DS-2TD2617B-6/PA Effective Range: 4.9 to 9.8 ft.	
		Long-range Bullet Camera DS-2TD2636B-13/P Effective Range: 8.2 to 23 ft	The long-range bullet camera provides a longer and wider effective measurement range with a higher thermographic resolution. Equipped with face detection and mask detection. Model does not have a built-in speaker with voice alarms.
		Network Video Recorder DS-7608NI-I2/8P-2TB	The NVR rapidly deploys with the cameras to provide a simple visual interface for monitoring temperature alarms. This NVR also powers the camera via PoE and it can record camera video and alarms on the included 2 TB of storage.
		22" Monitor DS-D5022QE-B	This Full HD 22" LED-Backlit LCD monitor connects directly to the NVR via HDMI to show the operator which individual has an elevated skin-surface temperature.

ELEVATED SKIN-SURFACE TEMPERATURE SCREENING SOLUTIONS



BEST		
<p>KEY FEATURES</p> <ul style="list-style-type: none"> 0.5° F Accuracy Smart Measurement Mask Enforcement Automated Voice Alarms Rapid Screening Identify Verification Multi-site Management 	<p>Short-range Turret Camera DS-2TD1217B-3/PA Effective Range: 2.6 to 4.9 ft.</p>	<p>The short-range turret and mid-range bullet cameras can be mounted on a tripod for a portable solution or affixed to a wall or ceiling for a long-term solution. The cameras can measure skin-surface temperature of up to 30 faces at one time, providing faster, more accurate screening. Additional features include face mask detection and automated voice alarms. Limiting temperature measurements solely to detected faces reduces false alarms from other heat sources such as a cup of coffee.</p>
	<p>Mid-range Bullet Camera DS-2TD2617B-6/PA Effective Range: 4.9 to 9.8 ft.</p>	<p>The long-range bullet camera provides a longer and wider effective measurement range with a higher thermographic resolution. Equipped with face detection and mask detection. Model does not have a built-in speaker with voice alarms.</p>
	<p>Long-range Bullet Camera DS-2TD2636B-13/P Effective Range: 8.2 to 23 ft</p>	<p>The turret and bullet thermographic cameras are able to continuously calibrate temperature measurement, based on the detected radiation from this source, to achieve accuracy of $\pm 0.5^{\circ}$ F.</p>
	<p>Blackbody Calibration Source DS-2TE127-G4A</p>	<p>The special DeepinMind NVR interface displays temperature and face mask statuses with statistics. Additional benefits include identity verification and stranger alarm even when face masks are worn. Voice alarms are available through HDMI or audio output.</p>
	<p>DeepinMind NVR IDS-9632NXI-I8/X(B)</p>	<p>This specialized video surveillance PoE switch with plug-and-play operation provides stable power and network connectivity to the cameras at extended distances up to 984 ft. (300 m).</p>
	<p>16-PoE-Port Switch DS-3E0318P-E2</p>	<p>HikCentral Professional provides a powerful, flexible and efficient central management system for all your cameras across one to many locations using a server-client architecture. The client interface provides local monitoring, instant alarm popups, temperature measurement alarm reports, quick record-searching and exporting.</p>
	<p>HikCentral Professional CMS HikCentral-VSS-Base/16Ch</p>	

Applications



Manufacturing



Retail



Commercial Real Estate



Healthcare



Education

HikCentral Professional

Video Surveillance System Base Licenses
HikCentral-VSS-Base/4Ch – Includes 4 camera licenses
HikCentral-VSS-Base/16Ch – Includes 16 camera licenses
HikCentral-VSS-Base/64Ch – Includes 64 camera licenses
HikCentral-VSS-Base/HW/64Ch – Includes 64 camera licenses with preloaded server
HikCentral-VSS-Base/300Ch – Includes 300 camera licenses
HikCentral-VSS-Base/HW/300Ch – Includes 300 camera licenses with preloaded server
Video Surveillance System Expansion License
HikCentral-VSS-1Camera – Add one camera to a VSS base license


Video Surveillance Hard Drives

	HK-HDD2T – 2 TB HDD
	HK-HDD4T – 4 TB HDD
	HK-HDD8T – 6 TB HDD
	HK-HDD8T – 8 TB HDD
	HK-HDD12T – 12 TB HDD
Surveillance grade 3.5" hard disk drives Compatible with network video recorders	

Handheld Camera Bracket Diagram



Bullet Camera Bracket Diagram



Turret Camera Bracket Diagram

