

NA-KB6013-WIP Wi-Fi Doorbell



- Video Intercom with Audio-Visual Communication via Mobile App
- High Performance CMOS, up to 1080p
- H.264 Video Compression
- Ultra-Wide Angle (180°)
- IR with 16 Feet (5 Meter) IR Range
- High-Performance Embedded SOC Processor
- Noise Suppression and Echo Cancellation
- Voice Prompt
- IP 65

Hikvision's NA-KB6013-WIP Wi-Fi Doorbell is an audio/video doorbell with a high resolution camera and remote communication through its mobile phone app (IOS and Android).

The NA-KB6013-WIP features motion detection and video recording, storage and playback via an on-board microSD card, a backlight indicator, a replaceable faceplate, and a reset button.

The unit can be connected to a mechanical chime, and volume is adjustable through the app. Online upgrades are supported via the mobile app.

Available Models

NA-KB6013-WIP

Accessories (Optional)

DS-KPB01 Power Booster



Specifications

NA-KB6013-WIP		
System	Processor	High-performance embedded SOC processor
	Operation System	Embedded Linux operation system
Camera	Image Sensor	CMOS 2 MP HD color camera
	Light Sensitivity	Low illumination
	Lens	Focal length: 1.96 mm, f/2.2
	Field of View	180° horizontal, 96° vertical
Video	Video Compression Standard	H.264
	Video Streaming	Dual stream Main stream: maximum 1080p @ 30 fps, sub-stream: VGA @ 30 fps
	Anti-Flicker Frequency	50 Hz, 60 Hz
	Wide Dynamic Range	WDR
Audio	Audio Streaming	Two-way, full duplex
	Audio Input	Built-in omnidirectional microphone
	Audio Output	Built-in loudspeaker
	Audio Compression Standard	G.711 U
	Audio Compression Rate	64 Kbps
Light Supplement	Audio Quality	Noise suppression and echo cancellation
	Light Supplement Mode	IR supplement, IR distance: 5 meters
Network	Wavelength	940 nm
	Network Protocol	TCP/IP, RTSP
Event	Network Interface	1 wireless interface (wireless network card), supporting 2.4 GHz
	Motion Detection	Supported
Alarm	Motion Detection Alarm	Supported
Device Interfaces	MicroSD Card	Maximum 128 GB
	Button	1 call button, 1 reset button
General	Ingress Protection Level	IP65
	Power Supply	16 VAC to 24 VAC
	Power Frequency	50 Hz to 60 Hz
	Power Consumption	Maximum 12 W
	Working Temperature	-30° to +50° C (-22° to 122° F)
	Working Humidity	10% to 90%
	Dimensions	4.82" x 1.81" x 1.11" (122.4 mm x 45.9 mm x 28.1 mm)

Typical

