

DS-2CE56D7T-AITZ

HD1080p Motorized VF EXIR Indoor Dome Camera

- 1/2.7" (2 MP) High-Performance CMOS
- Analog HD Output, Up to 1080p Resolution
- 2.8 mm to 12 mm Motorized Vari-Focal Lens
- True Day/Night
- OSD Menu, DNR, Smart IR
- True WDR, Up to 120 dB
- EXIR Technology, Up to 98 ft (30 m) IR Range
- Up-the-Coax (HIKVISION-C)



The Hikvision DS-2CE56D7T-AITZ indoor dome camera provides high definition analog output up to 1080p. TurboHD means that the analog signal can be sent over existing RG6 coaxial cable, eliminating the need to run new cables for high definition video.

EXIR is Hikvision's proprietary IR extended range technology, which has a range of 98 feet (30 meters). Smart IR varies IR output based on the zoom setting.

The motorized 2.8 mm to 12 mm vari-focal lens allows convenient remote use. True WDR (Wide Dynamic Range) of 120 dB ensures images will be optimal, no matter what the lighting conditions.

This camera also features a range of Smart functions, including line crossing, intrusion, and region entrance and exit, benefitting users with great improvements on security efficiency and, more importantly, with key events and objects being recorded for further forensic needs.


Available Models: DS-2CE56D7T-AITZ










Specifications

DS-2CE56D7T-AITZ	
Camera	
Image Sensor	1/2.7" (2 MP) CMOS image sensor
Signal System	PAL/NTSC
Effective Pixels	1928 x 1088
Minimum Illumination	0.01 lux @ (f/1.2, AGC on), 0 lux with IR
Shutter Speed	1/25 (1/30)s to 1/50,000s
Lens	Motorized VF lens; 2.8 mm to 12 mm Angle of view: 35.1° to 114.5°
Lens Mount	Φ14
Day/Night	ICR
3-Axis Positioning	Pan: 0° to 355°; tilt: 0° to 75°; rotate: 0° to 355°
Synchronization	Internal synchronization
WDR	120 dB
Video Frame Rate	1080p @ 25 fps/1080p @ 30 fps (PAL/NTSC)
HD Video Output	1 analog HD-TVI output
S/N Ratio	>62 dB
Menu	
AGC	Supported
D/N Mode	Color/BW/Smart
White Balance	ATW/MWB
BLC	Supported
Functions	Wide Dynamic Range, digital noise reduction, mirror, Smart IR
General	
Operating Conditions	-40° C to 60° C (-40° F to 140° F), humidity 90% or less (non-condensing)
Power Supply	12 VDC ±15%, 24 VAC ±15%
Power Consumption	Maximum 6.5 W
IR Range	Up to 98 ft (30 m)
Communication	Up-the-Coax, protocol: HIKVISION-C (HD-TVI output)
Dimensions	Φ5.35" × 4.02" (Φ136 mm × 102 mm)
Weight (approximate)	1.32 lb (600 g)

Dimensions



Accessories

						
CPM + PC130 Ceiling Pendant Mount + 130 mm Pendant Cap	CM Corner Mount	WML + PC130 Wall Mount Long + 130 mm Pendant Cap	PM Vertical Pole Mount	RCM-3 Recessed Ceiling Mount	DS-1H18 Video Balun	X41T Camera Tester